

UVNIUM™

Acoustic Felt

The sound insulation and absorption of spaces is the center of attention.

The reverberation time is usually shortened to improve the acoustics.

This sublimation suitable acoustic panel provides optimal absorption and is easy to process.

The absorption materials ensure that the disturbing reflection is counteracted and the reverberation time is regulated.

The plate is made from 100% recycled PET bottles without chemical binders or raw materials. Contour cutting of the image is one of the extra options

Applications:

The acoustic panel can be used as a ceiling plate and wall plate.

The acoustic felt plate can be glued to walls with mounting kit.

Mechanical mounting by means of stapling or nailing is also possible

Specifications:

Dimensions: (H x W x D) 2,440 x 1,220 x 9 mm (tolerance surface +/- 5 mm)

Maximum dimensions 2240 x 3660 x 25 mm, other thicknesses and colors on request.

Colors: 30 basic colors colored through and through, full color felt: endless

Material: 100% (recycled) PET fibers.

Other: 100% recyclable, environmentally friendly, flame resistant class B (EN 13501-1)

Rot resistant, insensitive to dust mites, fungi.

Contains no chemicals, maximum sound absorption, UV resistant.

Sublimation Felt

Size	Color	Dim.	Thickness	
1220x2440	wit		9mm	
1220x2440	wit		12mm	
1220x2440	wit		24mm	

